




## AutoPilot™

- 7" interactive touch screen controls up to 24 fans
- Access and control your fans wirelessly from any web-enabled smart device
- Ties into existing fire suppressions system to shut down in case of emergency
- Set automatic mode to auto-adjust fan speed and maintain temperature settings
- Password enabled with multi-level access
- Create custom names for each fan



## Touch 'N' Go Premier

- Operates up to 10 fans | Operates one fan
- Operate fan in either forward (cooling) or reverse (destratification)
- 0 - 100% speed control
- Fully digital interface
- Visual indicators of speed and direction
- Password lockout capability



## VLD

- Digital interface
- Easily mounted to wall
- Control each fan individually
- Operate fan in either forward (cooling) or reverse (destratification)
- Manually control each fan's forward speed
- 3-digit, 7-segment display and 3-button keyboard interface



## Manual Single Fan

- Operates one fan (single yoke)
- Operate fan in either forward (cooling) or reverse (destratification)
- Easily mounted to wall
- Manually control speed of each fan

Note: double yoke and triple yoke available



## IDFC Single Fan


- Easily mounted to wall enclosure
- Control each fan individually
- Operate your fans in either forward (cooling) or reverse (destratification)
- Manually control each fan's speed



## Ultralite

- Easily mounted to wall
- Control each fan individually
- Operate fan in forward direction only
- Manually control each fan's forward speed





FEATURES	AUTOPILOT™	TOUCH 'N' GO PREMIER	VLD	MANUAL SINGLE	IDFC SINGLE	ULTRALITE
<b>Gearbox Part #</b>	BP-260	BP-773.#	BP-775	BP-777	BP-791	BP-789
<b>Direct Drive Part #</b>	BP-260	BP-773.#	BP-775	DP-779	DP-793	BP-789
<b># of Fans Controlled</b>	Up to 24	Up to 10 (#)	1	1	1	1
<b>Power Supply</b>	90-250V 50/60Hz	External 24V (Supplied)	110-230 VAC ±10% / 50-60 Hz	0-10V DC Analog from VFD	0-10V DC Analog from VFD	0-10V DC Analog from VFD
<b>Connections</b>	RS485	6-Core Shielded Wire	2-Core Shielded Wire	6-Core Shielded Wire	6-Core Shielded Wire	5-Core Shielded Wire
<b>Dimensions</b>	6.0" L	7.125" L	3.125" L	5" L	5" L	3.125" L
	13.5"W	4.75" W	2.125" W	3" W	3" W	3.125" W
	10.0" H	0.50" H	2.25" H	2" H	2" W	2.5" H
<b>Language Protocol</b>	Modbus RS485	0-10V CAN	0-10V Signal	0-10V Signal	0-10V Signal	0-10V Signal
<b>Temperature Inputs</b>	Two local and up to 48 remote inputs	N/A	N/A	N/A	N/A	N/A
<b>Enclosure</b>	ABS Plastic	ABS Plastic	ABS Plastic	ABS Plastic	ABS Plastic	ABS Plastic
<b>User Interface</b>	7" Digital Touchscreen	7" Digital Touchscreen	Digital	Rotary Dial	Rotary Dial	Rotary Dial
<b>Protection Rating</b>	NEMA 4X IP65	IP30	IP44 IP54	NEMA 4X IP65	NEMA 4X IP65	IP44 IP54
<b>Max Cable Length</b>	4,000 ft.	1,640 ft.	300 ft.	300 ft.	300 ft.	300 ft.
<b>Provided Cable Length</b>	Field Supplied	Field Supplied	Field Supplied	100 ft.	Field Supplied	Field Supplied
<b>Direction</b>	Forward	Forward	Forward	Forward	Forward	Forward
	Reverse	Reverse		Reverse	Reverse	
<b>BacNet VFD Protocol</b>	Available	Available	Available	Available	Available	Available
<b>ModBus VFD Protocol</b>	Standard	Standard	Standard	Standard	Standard	Standard

Certification



AUTHORIZED DEALER

**BLUE GIANT®**  
BLUE GIANT EQUIPMENT CORPORATION

**Corporate** 410 Admiral Blvd  
Mississauga, ON, Canada L5T 2N6  
t 905.457.3900 f 905.457.2313

**USA** 24501 Hoover Rd  
Warren, MI 48089  
[www.bluegiant.com](http://www.bluegiant.com)