

FOAM FRAME SHELTER

Model	BGDSHF (US)	BG600 (CAN)
Fits Standard Door Size	10.5' x 10.5' (3.2 x 3.2 m)	
Seals Trailer Heights	12' - 13.5' (3.7 - 4.1 m) - on typical 4' (1.2 m) dock height	
Components	One (1) head curtain, two (2) side curtains, one (1) head frame, two (2) foam base pads, two (2) side supports, two (2) bottom draft pads, one (1) trim angle	
Frame	Pressure-treated lumber covered with translucent sheeting. Peaked center to allow for drainage. Minimum 1.5" x 2.5" (40 x 65 mm) galvanized trim angle. Standard projection of 18" (457 mm)	
Side Pad Material	Polyurethane foam core with 98% memory, maintaining flexibility at -40°C / -40°F, bonded to kiln dried treated lumber backing	
Head Curtain	138" (3,505 mm) wide with 36" (610 mm) drop with 20" x 10" (508 x 254 mm) protective pleat/flaps at impact area. 40oz. premium grade vinyl	
Side Curtains	24" wide x 120" high (610 x 3,048 mm) with 4" x 24" (102 x 610 mm) heat sealed yellow guide stripes. Polyester base with 40oz. premium grade vinyl	
Side Pads	8" wide x 126" high x 18" projection (203 x 3,200 x 457 mm). 22oz. premium grade vinyl	
Mounting Hardware	Galvanized	
Warranty	Subject to standard limitations on liability. See www.bluegiant.com/support/product-warranty for more information	

OPTIONAL FEATURES

- **Curtain:** 22/50oz. premium grade vinyl or ArmorShield™ or 40oz. Thermalon
- **Pleat/Flap:** 22/50oz. premium grade vinyl or ArmorShield™ or 40oz. Thermalon
- Reflective guides
- Combo unit options
- Additional projection (per inch)
- Gussets in head curtains
- Wood build-out box
- Double layer of fabric on the bottom 24" (610 mm) of curtain: 22/40/50oz. ArmorShield™ or 40oz. Thermalon
- Additional width in side curtains (per inch)
- Additional drop in head curtain (per inch)
- Reinforced edges on side pads
- Additional header width
- Additional side frame height
- Galvanized steel head frame with galvanized sheeting